



WALLPAPER ADHESIVE POWDER SPECIAL

WALLPAPER PASTE ON THE BASIS OF HIGH-QUALITY CELLULOSE AND SYNTHETIC RESIN



PRODUCT DESCRIPTION

Wallpaper paste on the basis of high-quality cellulose and synthetic resin.

FIELD OF APPLICATION

Suitable for applying all kinds of heavy, extra heavy and special wallpapers, such as woodchip, (heavy) duplex, smooth vinyl, structured vinyl, acrylic, strippable, washable, jute fabric, foamed, embossed, textile and photo wallpapers.

PROPERTIES

- No clumping
- Non-staining
- Apply directly onto the wall
- Easy to apply
- Easily correctable
- Super-strong
- Ready for use within 10 minutes
- Airtight packaging
- Permanently fresh paste
- Moisture resistant

PREPARATION

Working Conditions: Do not apply at temperatures below +10 °C and/or relative humidity higher than 70 %.

Surface Requirements: For an optimal result the surface must be porous, solid, clean, permanently dry, smooth, dust- and grease-free.

Preliminary Surface Treatment: Remove the old wallpaper using a wallpaper removal agent, then clean the surfaces in order to remove any remaining paste, grease or dust. Fill holes and cracks with wall filler to make the surface even and then coat any stains so that they do not show on the surface of the wallpaper. Prime highly absorbent surfaces first with diluted wallpapering paste (20 % water). Allow this primer layer to dry for at least 2 hours. Sand non-absorbent surfaces (e.g. latex layer) by initially opening up and then making the surface dust-free.

Tools: Pasting brush, bucket, stirring stick, wallpaper table. Clean tools immediately after use with water.

APPLICATION

Directions for use:

Add the powder in small quantities to cold water while vigorously stirring until a lump-free paste is obtained. Let the paste rest and stir up vigorously again after 10 minutes. The paste is now ready to use.

- Coat the wallpaper strips thoroughly and evenly with a fur roller or brush, making sure the edges are properly covered. Fold the strips double and allow the paste to soak in following the instructions of the wallpaper manufacturer. Roll vinyl wallpaper after folding to prevent the edges from drying out. Apply a strip of paper to the wall and brush it smooth using a plastic spatula or brush. Always smooth the wallpaper from the centre to the edges, and from top to bottom. Make sure that the seams are properly pressed against each other. Mixing ratio:
 - Pre-gluing: 8 liters of water / 70m²
 - Heavy, special, dry strippable, washable and raw material wallpaper: 4 liters of water / 4-5 rolls / 20-25m²
 - Extra heavy, vinyl and jute fabric wallpaper: 3 liters of water / 3 rolls / 15m² Water temperature 5 - 10°C

Stains/residue: Remove traces of paste immediately by dabbing with a clean, dry cloth. Dried paste on the surface of the wallpaper can be removed by dabbing with a clean, damp cloth.

Advice: Ready-made paste remains workable for several days when stored tightly sealed.

Points of attention: Always hang wallpaper in accordance with the manufacturer's instructions.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.



WALLPAPER ADHESIVE POWDER SPECIAL

WALLPAPER PASTE ON THE BASIS OF HIGH-QUALITY CELLULOSE AND SYNTHETIC RESIN

TECHNICAL SPECIFICATIONS

Chemical base:	Methyl cellulose and copolymer
Colour:	White
Dilute:	Prepare or mix with water.
Moisture resistance:	Good

PHYSIOLOGICAL PROPERTIES

Wallpaper Paste is physiologically safe.

STORAGE CONDITIONS

Close container properly and store in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.