



# FLOORING ADHESIVE

READY-TO-USE ADHESIVE FOR FLOOR COVERINGS, LINOLEUM AND WALL CORK



## PRODUCT DESCRIPTION

Ready-to-use adhesive for floor coverings, linoleum and wall cork. Waterbased adhesive.

## FIELD OF APPLICATION

Suitable for bonding floor coverings and carpet tiles with jute, felt or textile backing, linoleum and wall cork on porous surfaces such as cement, concrete and wood.

## PROPERTIES

- Easy to apply
- Solvent-free
- Not moisture resistant

## PREPARATION

**Working Conditions:** Do not apply at temperatures below +15 °C and/or relative humidity higher than 65 %.

**Surface Requirements:** The surface must be clean, dry, free of dust and grease.

**Preliminary Surface Treatment:** First level damaged or uneven floors.

**Tools:** Glue spreader No. 2.

## APPLICATION

**Coverage:** 2-3 m<sup>2</sup>/kg

### Directions for use:

Spread the glue (clean, dry and grease-free surface) evenly with a glue spreader. Place floor covering, linoleum or wall cork in the still wet adhesive within about 15 minutes and press or roll firmly. During these 15 minutes, adjustments can still be made. The adhesive joint can be loaded after 24-48 hours.

**Stains/residue:** Remove adhesive residues immediately with water. Dry adhesive residue can only be removed mechanically.

**Points of attention:** When bonding to wooden surfaces endorsement of the seams can occur. The adhesive bond can only be loaded after curing. The smell of the glue disappears after curing. We recommend to always observe the instructions of the manufacturer.

## TECHNICAL SPECIFICATIONS

Chemical base:	Sulfite lye
Colour:	Brown
Density approx.:	1.61 g/cm <sup>3</sup>
Drying/Curing time approx.*:	24-48 hours
Final bond strength after:	24
Minimum temperature resistance:	-20 °C
Maximum temperature resistance:	50 °C
Moisture resistance:	Nil
Open time approx.:	15 minutes
pH-value approx.:	8,0-9,0
Solid matter approx.:	79 %
Viscosity:	Pasty
Water resistance:	Nil

\* Curing time may vary depending on a.o. surface, product quantity used, humidity level and ambient temperature.

## STORAGE CONDITIONS

Store in tightly closed container in a dry, cool and frost-free place.

Our advice is based on extensive research and practical experience. However, in view of the large variety of materials and the conditions under which our products are applied, we assume no responsibility for the results obtained and/or any damage caused by the use of the product. Nevertheless, our Service Department is always at your disposal for any advice needed.